

PRODUCT	EPISOL® AQ PAINT	EPISOL® RP	EPILINE PROTECT	EPISOL® RP NV	EPISOL® DESIGNTOP SF	EPISOL® PU 43 OP EL	EPISOL® PU 43 OP MAT	EPISOL® PU TOPCOAT WB	POLYAC® 61	POLYAC® 62	POLYAC® 64 AF	POLYAC® 65	
BASE RESIN	EPOXY	EPOXY	EPOXY	EPOXY	EPOXY	PU	PU	PU	PMMA	PMMA	PMMA	PMMA	
DESCRIPTION	High built waterbased epoxy coating	Chemical resistant universal epoxy coating for floors and walls	High-grade sprayable rigid epoxy liner, applicable on dry and moist surfaces	High built epoxy coating for dry surfaces	Sealer and top coat for epoxy mortar flooring	Antistatic top coat	Wear resistant polyurethane top coat	Waterbased top coat	Top coating for POLYAC® systems	Chemical resistant top coating for POLYAC® systems	Fire retardant top coating for POLYAC® systems	Flexible top coating for POLYAC® systems	
COMPLIES WITH VOC REGULATION	VOC			VOC	VOC	VOC	VOC	VOC					
APPLICATIONS	Garages, workshops, warehouses	■	■	■	■	■	■	■	■	■	■	■	
	Pharmaceutical industries				■	■	■	■					
	Electric power plants	■	■		■	■	■	■					
	Food processing industry	■			■	■	■	■	■	■			
	Storage areas for hazardous goods	■	■	■	■	■	■	■		■			
	Hospitals					■	■	■					
	Battery rooms		■				■	■		■			
	Public areas	■			■	■	■	■					
	Breweries	■			■	■	■	■		■			
	Heating/boiler	■	■		■	■			■				
	Basement	■	■	■	■								
	Home	■							■				
	Laundry	■			■					■	■		
	Staircases	■				■				■	■		
	Retention basins		■	■						■			
	Freeze/cold room									■			■
	Non-walkable roofs									■		■	■
Toplayer parking deck									■		■		
Drainage and inspection wells			■										
Chemical resistance	<i>See chemical resistance list</i>												
UV resistance	++				+	++	++	++	+	+	+	+	
Abrasion resistance	+	+		+	+	++	++	++	+	++			
Impact resistance	+	+			+	++	++	++			+	+	
Can be applied inside and outside	+	+	+						+	+	+	+	
Appearance	Satin	Glossy	Glossy	Glossy	Glossy	Matt	Matt	Matt	Matt	Matt	Matt	Matt	
Transparent					+		+		+	+	+	+	
Can be coloured	+			+		+	+						
Solvent-free	+		+		+			+	+	+	+	+	
No tyre marks													
Fast curing			+						+	+	+	+	
Min. processing temperature <5°C									+	+	+	+	
Easy maintenance	+	+		+	+	+	+	+	+	+	+	+	
Adhesion	++	++	++	++	++	++	++	++	++	++	++	++	
Water-dilutable	+												
Water vapour permeable	+						+						
Waterbased	+							+					
FIRE RETARDANT STANDARD	B ₁ -s1						B ₁ -s1				B ₁ -s1 & B _{nor} (t1-t2)		
CE CERTIFICATE	EN 13813	EN 13813	EN 13813	EN 13813	EN 13813	EN 13813	EN 13813	EN 13813	EN 13813	EN 13813	EN 13813	EN 13813	