

	PRODUCT	EPICOL INJ LV	VIBROX	VIBROX XL	POLYAC® M	RESIPOX®	POLYAC® 53
	BASE RESIN	EPOXY	EPOXY	EPOXY	PMMA	EPOXY	PMMA
	DESCRIPTION	Low-viscosity epoxy resin for concrete injection	Epoxy casting mortar 4 to 40 mm	Epoxy casting mortar 3 to 50 cm	POLYAC® mortar system	Fast curing epoxy repair mortar	Resin for POLYAC® seamless coving
APPLICATIONS	Anchoring	■		■			
	Used for wooden supporting structures						
	Wharf and jetty poles						
	Grouting of small layer thicknesses	■	■				
	Grouting of large layer thicknesses			■			
	Seamless plinths					■	■
	Levelling				■	■	
	Can be used both horizontally and vertically					■	
	Vibration-free grouting		■	■			
CHARACTERISTICS	Chemical resistance	<i>See chemical resistance list</i>					
	Can be applied inside and outside	+	+	+	+	+	
	Mechanical strength		+	+	+	+	
	Pressure resistance	+	+	+	+	+	
	Impact resistance		+	+			
	Long processing time	+	+				
	Waterproof / liquid tight		+	+	+	+	+
	Solvent-free	+	+	+	+	+	+
	Reactivity				+		+
	Fast Curing				+	+	+
	No shrinkage	+	+	+		+	
	Min. processing temperature <5°C				+		+
CE CERTIFICATE	EN 13813	EN 1504-3	EN 1504-3	EN 13813	EN 13813 - EN 1504-3	EN 13813	
PRIMERS	n/a	n/a	n/a	POLYAC® 12 POLYAC® 14 POLYAC® 15 POLYAC® 18	RESIPOX® PRIMER EPISOL® UNIVERSAL	POLYAC® 12 POLYAC® 14 POLYAC® 15 POLYAC® 18	