

	PRODUCT	POLYAC® BDM-AL	POLYAC® BDM-M	POLYAC® BDM-HD
	BASE RESIN	PMMA	PMMA	PMMA
	DESCRIPTION	Self-levelling waterproofing membrane	Self-levelling waterproofing membrane	Liquid waterproofing membrane for industrial spray applications
APPLICATIONS	Renovation of existing water proofing layers	■	■	■
	Roofs	■	■	■
	Parking roofs	■	■	■
	Terraces	■	■	■
	Bridges		■	■
	Reservoirs		■	■
CHARACTERISTICS	Chemical resistance	<i>See chemical resistance list</i>		
	Can be used horizontally and vertically		+	+
	Resistant to thermal shock	+	+	+
	Durability	+	+	+
	Flexible	+	+	+
	Long processing time			+
	Crack covering	+	+	+
	Reactivity	+	+	+
	Fast Curing	+	+	+
	Applicable at low temperatures	+	+	+
	Resistant to thawing salt	+	+	+
CE CERTIFICATE	EN 1504-2	EN 1504-2	EN 1504-2	
PRIMERS	POLYAC® 12, 14, 15, 18	POLYAC® 12, 14, 15, 18	POLYAC® 12, 14, 15, 18	
PRIMER INTERLAYER (BDM AND HOT MIX ASPHALT)	POLYAC® 17	POLYAC® 17	POLYAC® 17	
TOPLAYERS	POLYAC® 61, 64 AF, 65	POLYAC® 61, 64 AF, 65	POLYAC® 61, 64 AF, 65	