

1 SECTION 1: Identification of the substance/mixture and of the company/undertaking:

1.1 Product identifier:

Episol Floorline 0,5-1,0 mm B

1.2 Relevant identified uses of the substance or mixture and uses advised against:

For professional use only

Concentration in use: /

1.3 Details of the supplier of the safety data sheet:

RESIPLAST NV

Gulkenrodestraat 3

B2160 Wommelgem

Phone: 033200211 — Fax: 033226380

E-mail: info@resiplast.be — Website: <http://www.resiplast.be/>

1.4 Emergency telephone number:

+32 70 245 245

2 SECTION 2: Hazards identification:

2.1 Classification of the substance or mixture:

Classification of the substance or mixture in accordance with regulation (EU) 1272/2008:

H302 Acute tox. 4 H314 Skin Corr. 1B H317 Skin Sens. 1 H412 Aquatic Chronic 3

2.2 Label elements:

Pictograms:



Signal word:

Danger

Hazard statements:

H302 Acute tox. 4: Harmful if swallowed.
H314 Skin Corr. 1B: Causes severe skin burns and eye damage.
H317 Skin Sens. 1: May cause an allergic skin reaction.
H412 Aquatic Chronic 3: Harmful to aquatic life with long lasting effects.

Precautionary statements:

P260: Do not breathe dust/vapours/spray.
P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310: Immediately call a POISON CENTER or doctor.
P405: Store locked up.
P501: Dispose of contents/container in accordance with local/regional/national/international regulations.

Contains:

m-phenylenebis(methylamine) Isophoronediamine Benzyl alcohol

2.3 Other hazards:

None

3 SECTION 3: Composition/information on ingredients:

Benzyl alcohol	≤ 60 %	CAS number: 100-51-6 EINECS: 202-859-9 REACH Registration number: 01-2119492630-38 CLP Classification: H302 Acute tox. 4 H319 Eye Irrit. 2 H332 Acute tox. 4
Isophoronediamine	≤ 30 %	CAS number: 2855-13-2 EINECS: 220-666-8 REACH Registration number: 01-2119514687-32 CLP Classification: H302+H312 Acute tox. 4 H314 Skin Corr. 1B H317 Skin Sens. 1 H412 Aquatic Chronic 3
m-phenylenebis(methylamine)	≤ 10 %	CAS number: 1477-55-0 EINECS: 216-032-5 REACH Registration number: 01-2119480150-50 CLP Classification: H302 Acute tox. 4 H314 Skin Corr. 1B H317 Skin Sens. 1 H332 Acute tox. 4 H412 Aquatic Chronic 3

Styrenated phenol	≤ 5 %	CAS number: 61788-44-1 EINECS: 262-975-0 REACH Registration number: 01-2119980970-27 CLP Classification: H315 Skin Irrit. 2 H317 Skin Sens. 1 H411 Aquatic Chronic 2
salicylic acid	≤ 3 %	CAS number: 69-72-7 EINECS: 200-712-3 REACH Registration number: 01-2119486984-17 CLP Classification: H302 Acute tox. 4 H318 Eye Dam. 1 H361d Repr. 2

For the full text of the H phrases mentioned in this section, see section 16.

4 SECTION 4: First aid measures:

4.1 Description of first aid measures:

Always ask medical advice as soon as possible should serious or continuous disturbances occur.

Skin contact:	Remove contaminated clothing, rinse skin with plenty of water and immediately transport to hospital.
Eye contact:	Thoroughly rinse with water (contact lenses to be removed if this is easily done) then take to physician.
Ingestion:	Rinse mouth, do not induce vomiting, take to hospital immediately.
Inhalation:	Let sit upright, fresh air, rest and take to hospital.

4.2 Most important symptoms and effects, both acute and delayed:

Skin contact:	Caustic, redness, pain, serious burns
Eye contact:	Caustic, redness, blurred vision, pain
Ingestion:	Caustic, lack of breath, vomiting, blisters on lips and tongue, burning pain in mouth and throat, gullet and stomach
Inhalation:	Headache, dizziness, nausea, drowsiness, unconsciousness

4.3 Indication of any immediate medical attention and special treatment needed:

None

5 SECTION 5: Fire-fighting measures:

5.1 Extinguishing media:

CO₂, foam, powder, sprayed water

5.2 Special hazards arising from the substance or mixture:

None

5.3 Advice for firefighters:

Extinguishing agents to be avoided: None

6 SECTION 6: Accidental release measures:

6.1 Personal precautions, protective equipment and emergency procedures:

Do not walk into or touch spilled substances and avoid inhalation of fumes, smoke, dusts and vapours by staying up wind. Remove any contaminated clothing and used contaminated protective equipment and dispose of it safely.

6.2 Environmental precautions:

Do not allow to flow into sewers or open water.

6.3 Methods and material for containment and cleaning up:

Contain released substance, store into suitable containers. If possible, remove by using absorbent material.

6.4 Reference to other sections:

For further information, check sections 8 & 13.

7 SECTION 7: Handling and storage:

7.1 Precautions for safe handling:

Handle with care to avoid spillage.

7.2 Conditions for safe storage, including any incompatibilities:

Keep in a sealed container in a closed, frost-free, ventilated room.

7.3 Specific end use(s):

For professional use only





8 SECTION 8: Exposure controls/personal protection:

8.1 Control parameters:

Listing of the hazardous ingredients in section 3, of which the TLV value is known

/

8.2 Exposure controls:

Inhalation protection:	Use with sufficient exhaust ventilation. If necessary, use an air-purifying face mask in case of respiratory hazards. Use the ABEK type as protection against these troublesome levels.	
Skin protection:	Handling with nitril-gloves (EN 374). Breakthrough time: >480' Material thickness: 0,35 mm. Thoroughly check gloves before use. Take of the gloves properly without touching the outside with your bare hands. The manufacturer of the protective gloves has to be consulted about the suitability for a specific work station. Wash and dry your hands.	
Eye protection:	Keep an eye-rinse bottle within reach. Tight-fitting safety goggles. Wear a face shield and protective suit in case of exceptional processing problems.	
Other protection:	Wear impermeable clothing. The type of protective equipment depends on the concentration and amount of hazardous substances at the work station in question.	

9 SECTION 9: Physical and chemical properties:

9.1 Information on basic physical and chemical properties:

Melting point/melting range:	/
Boiling point/Boiling range:	205 °C — 272 °C
pH:	/
pH 1% diluted in water:	/
Vapour pressure/20°C,:	/
Vapour density:	Not applicable
Relative density, 20°C:	1.0600 kg/l
Appearance/20°C:	Liquid
Flash point:	/
Flammability (solid, gas):	Not applicable
Auto-ignition temperature:	435 °C
Upper flammability or explosive limit, (Vol %):	13.000 %
Lower flammability or explosive limit, (Vol %):	1.300 %
Explosive properties:	Not applicable
Oxidising properties:	Not applicable
Decomposition temperature:	/
Solubility in water:	Not soluble
Partition coefficient: n-octanol/water:	Not applicable
Odour:	characteristic
Odour threshold:	Not applicable
Dynamic viscosity, 20°C:	300 mPa.s
Kinematic viscosity, 40°C:	283 mm ² /s
Evaporation rate (n-BuAc = 1):	0.010

9.2 Other information:

Volatile organic component (VOC):	52.50 %
Volatile organic component (VOC):	583.000 g/l
Sustained combustion test :	/

10 SECTION 10: Stability and reactivity:

10.1 Reactivity:

Stable under normal conditions.

10.2 Chemical stability:

Extremely high or low temperatures.

10.3 Possibility of hazardous reactions:

None

10.4 Conditions to avoid:

Protect from sunlight and do not expose to temperatures exceeding + 50°C.

10.5 Incompatible materials:

Acids, alkalines, oxidants, reductants

10.6 Hazardous decomposition products:

Under recommended usage conditions, hazardous decomposition products are not expected.

11 SECTION 11: Toxicological information:

11.1 Information on toxicological effects:

H302 Acute tox. 4:	Harmful if swallowed.
H314 Skin Corr. 1B:	Causes severe skin burns and eye damage.
H317 Skin Sens. 1:	May cause an allergic skin reaction.

Calculated acute toxicity, ATE oral: 1 354.756 mg/kg

Calculated acute toxicity, ATE dermal: 3 000.000 mg/kg

Benzyl alcohol	LD50 oral, rat: 1 620 mg/kg LD50 dermal, rabbit: ≥ 5 000 mg/kg LC50, Inhalation, rat, 4h: 11 mg/l
Isophoronediamine	LD50 oral, rat: 1 030 mg/kg LD50 dermal, rabbit: 1 100 mg/kg LC50, Inhalation, rat, 4h: ≥ 50 mg/l
m-phenylenebis(methylamine)	LD50 oral, rat: 1 180 mg/kg LD50 dermal, rabbit: 3 100 mg/kg LC50, Inhalation, rat, 4h: 11 mg/l
Styrenated phenol	LD50 oral, rat: ≥ 5 000 mg/kg LD50 dermal, rabbit: ≥ 5 000 mg/kg LC50, Inhalation, rat, 4h: ≥ 50 mg/l
salicylic acid	LD50 oral, rat: 891 mg/kg LD50 dermal, rabbit: ≥ 5 000 mg/kg LC50, Inhalation, rat, 4h: ≥ 50 mg/l

12 SECTION 12: Ecological information:

12.1 Toxicity:

Benzyl alcohol	LC50 (Fish): 460 mg/L (72h) EC50 (Daphnia): 230 mg/L (48h) NOEC (Daphnia): 310 mg/L (72h) EC50 (Algae): 770 mg/L (72h)
Isophoronediamine	EC50 (Algae): 12 mg/L (Scenedesmus)(72h)

m-phenylenebis(methylamine)	LC50 (Fish): 87.6 mg/L (96h) EC50 (Daphnia): 87.6 mg/L (96h) EC50 (Algae): 20.3 mg/L (72h) EC50 (soil microorganisms): > 1000 mg/L (30min)
Styrenated phenol	LC50 (Fish): 5.6 mg/L (4d) NOEC (Fish): 1.9 mg/L (14d) EC50 (Daphnia): 1.44 - 4.6 mg/L (45h) EC50 (Algae): 1.5 mg/L (21d) NOEC (Algae): 115 - 200 µg/L (21d)
salicylic acid	EC50 (Daphnia): 870 mg/L (48h) EC50 (Algae): > 100 mg/L (72h)

12.2 Persistence and degradability:

No additional data available

12.3 Bioaccumulative potential:

No additional data available

12.4 Mobility in soil:

Water hazard class, WGK (AwSV): 1
Solubility in water: Not soluble

12.5 Results of PBT and vPvB assessment:

No additional data available

12.6 Other adverse effects:

No additional data available

13 SECTION 13: Disposal considerations:

13.1 Waste treatment methods:

Draining into the sewers is not permitted. Removal should be carried out by licensed services. Possible restrictive regulations by local authority should always be adhered to.

14 SECTION 14: Transport information:

14.1 UN number:

2735

14.2 UN proper shipping name:

UN 2735 Amines, liquid, corrosive, n.o.s. (mixture with m-phenylenebis(methylamine); Isophoronediamine) , 8, III, (E)

14.3 Transport hazard class(es):

Class(es): 8

Identification number of the hazard: 80

14.4 Packing group:

III

14.5 Environmental hazards:

Not dangerous to the environment

14.6 Special precautions for user:

Hazard characteristics: Risk of burns. Risk to the aquatic environment and the sewerage system.

Additional guidance:



15 SECTION 15: Regulatory information:

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Water hazard class, WGK (AwSV): 1
Volatile organic component (VOC): 52.500 %
Volatile organic component (VOC): 583.000 g/l
Composition by regulation (EC) 648/2004: Preservatives (Salicylic Acid)

15.2 Chemical Safety Assessment:

No data available

16 SECTION 16: Other information:

Legend to abbreviations used in the safety data sheet:

ADR:	The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE:	Acute Toxicity Estimate
BCF:	Bioconcentration factor
CAS:	Chemical Abstracts Service
CLP:	Classification, Labelling and Packaging of chemicals
EINECS:	European Inventory of Existing commercial Chemical Substances
LC50:	median Lethal Concentration for 50% of subjects
LD50:	median Lethal Dose for 50% of subjects
Nr.:	Number
PTB:	Persistent, Toxic, Bioaccumulative
TLV:	Threshold Limit Value
vPvB:	very Persistent and very Bioaccumulative substances

WGK:	Water hazard class
WGK 1:	Slightly hazardous for water
WGK 2:	Hazardous for water
WGK 3:	Extremely hazardous for water

Legend to the H Phrases used in the safety data sheet:

H302 Acute tox. 4: Harmful if swallowed. **H302+H312 Acute tox. 4:** Harmful if swallowed or in contact with skin.
H314 Skin Corr. 1B: Causes severe skin burns and eye damage. **H315 Skin Irrit. 2:** Causes skin irritation.
H317 Skin Sens. 1: May cause an allergic skin reaction. **H318 Eye Dam. 1:** Causes serious eye damage.
H319 Eye Irrit. 2: Causes serious eye irritation. **H332 Acute tox. 4:** Harmful if inhaled.
H361d Repr. 2: Suspected of damaging the unborn child. **H411 Aquatic Chronic 2:** Toxic to aquatic life with long lasting effects.
H412 Aquatic Chronic 3: Harmful to aquatic life with long lasting effects.

CLP Calculation method:

Calculation method

Reason of revision, changes of following items:

Section: 11

SDS reference number:

ECM-106467,00

This safety information sheet has been compiled in accordance with annex II/A of the regulation (EU) No 2015/830. Classification has been calculated in accordance with European regulation 1272/2008 with their respective amendments. It has been compiled with the utmost care. We cannot, however, accept responsibility for damage, of any kind, that may be caused by using these data or the product concerned. To use this preparation for an experiment or a new application, the user must carry out a material suitability and safety study himself.